

# SAFETY SHOWERS AND EYEWASH EQUIPMENT

## PREMIUM RANGE

Item Code	Description
H-EXP18GS85G	Emergency Combination Safety Shower with Eye/ Face Wash

Floor mounted emergency safety shower with eye/face wash unit in Marine 316 Stainless Steel. This ANSI compliant Combination Shower and Eye/face wash is ideal for use in applications not subject to high ambient operating temperatures.

The Stocked Model is Versatile and allows for Top or Mid-Level water Inlet at 1-1/4 BSP Female.

SPECIFICATIONS	
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute Eye wash: 12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	MINIMUM 5C / 41F MAXIMUM 55C / 131F

Please see page 42-43 for optional accessories

Item Code	Description
H-EXPSD18GS85G	Self-Draining Emergency Combination Safety Shower with Eye/ Face Wash

Floor mounted Self-draining emergency safety shower with eye/face wash unit in Marine 316 Stainless Steel. The design allows standing water to drain away from the standpipe to ensure the delivery of tepid (16-36c) water. The valve is situated directly above the water inlet; the bleed pipe is fitted above this so standing water can drain into the ground preventing stagnant water overheating from solar radiation and water contamination, thus removing the risk of further injury to the operator. Suitable for applications subject up to 45 degrees ambient temperatures in direct sunlight.

The stocked model's bottom water Inlet at 1-1/4 BSP Female.

SPECIFICATIONS	
OPERATING PRESSURE	2 to 6 BAR G / 29 to 87 PSI (higher supply pressures accommodated with the incorporation of the optional pressure reducing valve)
MINIMUM FLOW RATES	Shower: 76 L per minute / 20 US gal per minute Eye wash: 12 L per minute / 3 US gal per minute
AMBIENT OPERATING TEMPERATURE	MINIMUM 5C / 41F MAXIMUM 55C / 131F

Please see page 42-43 for optional accessories



# SAFETY SHOWERS AND EYEWASH EQUIPMENT

## PREMIUM RANGE

Wall Mounted, Pedestal Mounted, Handheld, Bench Mounted Eye/Face Wash in various materials to meet premium standards and conditions	
Item Code	Description
H-STD85G	Wall Mounted 316SS Eye/Face wash
H-STD85GSP	Pedestal Mounted 316SS Eye/Face wash

Open 316L stainless steel bowl, wall-mounted emergency eye/face wash featuring twin spray nozzles protected by dust covers. When activated via the push plate, the water jets lift off the dust covers. The eye wash diffusers are fitted with fine mesh strainers and individual flow controllers designed to give a gentle flow of aerated water. Unit is available Wall Mounted and Pedestal Mounted.



SPECIFICATIONS	
OPERATING PRESSURE	2.0 to 6 BAR G (29 to 87 PSI)
TEST PRESSURE	10.3 BAR G (149 PSI)
MINIMUM FLOW AT OPERATING PRESSURE	Shower: 76 litres/minute minimum (20 US Gallons). Eye/face wash: 12 litres/minute minimum (3 US Gallons)
MINIMUM AMBIENT OPERATING TEMPERATURE	5° C (41° F)
MAXIMUM AMBIENT OPERATING TEMPERATURE	35° C (95° F)

Please see page 42-43 for optional accessories

Emergency Handheld Eye, Face and Body Wash	
Item Code	Description
H-OPT1100	Wall Mounted Single Cup Optiflex
H-OPT1500	Wall Mounted Dual Cup Optiflex
H-OPT1600	Bench Mounted Dual Cup Optiflex

A range of wall or table mounted units, available with one or two nozzles, developed to suit hazardous environments where there is a risk of small spillages of chemicals or dangerous substances. The 1.5m of reinforced hose makes these handheld showers particularly useful for treating disabled personnel. The unique lock-on actuating button for ease of use meets European and international standards. Fitted with dust covers, a non-return valve and a built-in flow regulator.

